

10-26-00

A

ORIGINAL/CIP PATENT APPLICATION TRANSMITTAL LETTER

ATTORNEY'S DOCKET NO
RD-28,030

TO THE ASSISTANT COMMISSIONER FOR PATENTS:

Transmitted herewith for filing is the ☒ ORIGINAL ☐ CONTINUATION-IN-PART patent application of:
**METHOD FOR DEFINING AN EXPERIMENTAL SPACE AND METHOD AND SYSTEM FOR CONDUCTING
 COMBINATORIAL HIGH THROUGHPUT SCREENING OF MIXTURES**

Inventor(s)

For James Norman Cawse, Ronald James Wroczynski and Darchun Billy Yang

(Title of Invention)

☐ This is a Continuation-In-Part of Serial No. _____, filed _____, Attorney Docket No. _____

ENCLOSED ARE:

- ☒ Specification having 20 total pages.
- ☒ 5 sheets of ☐ formal ☒ informal drawings.
- ☒ Declaration. ☐ Unsigned Declaration.
- ☒ Information Disclosure Statement.
- ☐ Other _____
- ☒ An Assignment of the invention to General Electric Company with cover sheet.

The filing fee is calculated below:

	NUMBER FILED	NUMBER EXTRA	RATE	BASIC FEE \$710.00
TOTAL CLAIMS	25 - 20 =	5	x \$18.00	\$90.00
INDEPENDENT CLAIMS	3 - 3 =	0	x \$80.00	\$0.00
ADDITIONAL FEE FOR USE OF MULTIPLE DEPENDENT CLAIM(S) (once per application)			x \$270.00	
TOTAL FILING FEE				\$780.00

☒ Please charge \$780.00 to my Deposit Account No. 07-0868.☒ The Assistant Commissioner is hereby authorized to charge payment of all fees required under 37 CFR 1.16 or 1.17 or credit any overpayment to Deposit Account No. 07-0868.
10/25/00
 date

Noreen C. Johnson
 Attorney
Reg. No 38,929

Send Correspondence to:
 General Electric Company
 CRD Patent Docket Rm 4A59
 P.O. Box 8, Bldg. K-1 -Salamone
 Schenectady, New York 12301

"Express Mail" mailing label number EL641454767USDate of Deposit 10/25/00

Customer Number: 006147

Three copies of this form are enclosed

METHOD FOR DEFINING AN EXPERIMENTAL SPACE AND METHOD AND
SYSTEM FOR CONDUCTING COMBINATORIAL HIGH THROUGHPUT
SCREENING OF MIXTURES

BACKGROUND OF THE INVENTION

The present invention relates to a method for defining an experimental space and a method and system for conducting combinatorial high throughput screening of mixtures.

5 A gradient combinatorial study is a thorough method for studying an experimental space of a mixture. However, a thorough gradient study requires a relatively large number of experimental points. For example, even a simple commercial process may have three to five or more critical components, each of which can be chosen from a list of possibilities. These components can include reactants, solvents, additives and catalysts. As shown in FIG. 1, the number of
10 possible experimental points can become very large, depending on the number of intervals in the gradient. Accordingly, it may be necessary to search hundreds or thousands of combinations to find a handful of "leads," i.e., combinations that may lead to commercially valuable applications.

15 It is extremely difficult to examine all possibilities of such a complex space even with a very productive high throughput screening (HTS) system. The space can be decreased by decreasing the number of factors or by enlarging increments between test parameters. However both these approaches decrease accuracy and certainty of results. There is a need for an improved method to rapidly, yet effectively investigate a complex experimental space without diminishing accuracy or certainty of results.

BRIEF SUMMARY OF THE INVENTION

20 The present invention provides a method and system to investigate an experimental space without diminishing accuracy or certainty of results. The method comprises (A) defining a first experimental space comprising factors of at least two mixtures with at least one common factor, (B) defining a second experimental space

by deleting duplicate factor combinations from the first experimental space and (C) conducting an experiment on the second experimental space.

The system comprises a processor that (A) defines a first experimental space comprising factors of at least two mixtures with at least one common factor and (B) defines a second experimental space by deleting duplicate factor combinations from the first experimental space. The system also comprises a reactor and evaluator to select a best case set of factors from the second experimental space by a combinatorial high throughput screening (CHTS) method to select a best case set of factors from the second experimental space.

According to another embodiment of the invention, an experimental space that comprises a number of mixture combinations is defined by an algorithm, which expresses sum of terms:

$$V + \prod_{i=1}^T n_i \times I_T + \left(\sum_{i=1}^T \frac{1}{n_i} \right) \times \left(\prod_{i=1}^T n_i \right) \times [I_{(T-1)}]$$

for a ternary system ($T = 3$) or an algorithm for a succeeding T -nary system, determined from a previous term by: (a) adding an additional term which contains an additional summation, incremented over a next index from a starting point one unit higher than the first summation; (b) decrementing the subscript on I ; and (c) adding a value of n , indexed by the next index, to the inverse term.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a graph of the number of experiments needed for mixtures in ternary, quaternary and pentanary systems with various numbers of alternative components;

FIGs. 2 to 6 are triangular coordinate representations of ternary mixture studies;

FIG. 7 is a histogram of TON results; and

FIGs. 8, 9 and 10 are bar charts of TON results.

DETAILED DESCRIPTION OF THE INVENTION

According to the invention, a method and system are provided to efficiently conduct mixture experiments. A mixture experiment is an experiment in which response is assumed to depend only on the relative proportions of the ingredients or factors present in the mixture and not on the amount of the mixture. In a mixture experiment, if the total amount is held constant and the value of the response changes when changes are made in the relative proportions of the ingredients or factors making up the mixture, then the behavior of the response is said to be a measure of the joint blending property of the ingredients or factors in the mixture.

An experimental space is a preselected number of experimental runs to be performed at various predetermined combinations of proportions of factors. The space is the set of preselected combinations of proportions or blends of factors.

According to the invention, multiple factors in multiple systems are studied simultaneously. Duplicate experiments are omitted from the study. Hence the number of experiments required to separately study the systems is reduced. For example, several ternaries (three factor systems) or quaternaries (four factor systems) can be studied simultaneously and factors common to the multiple gradients can be eliminated. Single ternary and quaternary systems can be represented by two-dimensional triangular or three-dimensional tetrahedral graphs, respectively, where each vertex represents one of the factors, each edge represents mixtures of two factors and each face represents mixtures of three factors. Four factor combinations in quaternaries are considered interior (4-D) points. In effect, the use of multiple overlapping ternaries or quaternaries is obtained by overlapping common sides for the individual triangles in the ternary systems and common faces of the tetrahedra in the quaternary systems. Duplicate spaces for a given number of mixtures are determined and discarded and the resulting space simultaneously representing both or all the systems can be studied.

For example, FIG. 2 represents a ternary (ABC) mixture studied separately in 10% steps. Each intersection of lines in the gradient represents one mixture to be tested. FIG. 3 illustrates a simultaneous study of the FIG. 2 mixture and a second

ternary mixture (ABC') in 10% steps. In this case, A, B, and C represent components that have different roles in the mixture. C and C' have the same role in the mixture but are chemically distinct from each other. As shown in FIG. 3, the experimental spaces of the two ternary mixtures share AB combinations. The duplicate AB combination studies can be omitted with a reduction in experimental effort of $(11)/(66+66) = 8\%$. As shown in FIG. 4, an ABCA'B'C' system can be studied at 20% steps in 96 sample mixtures rather than 126 mixtures. This represents a 24% reduction in the experimental space size. Even more effective reduction occurs when eight spaces are combined as shown in FIG. 5. FIG. 5 shows a space represented by an unfolded octahedron where each factor is varied from 0 to 100%. If the systems are studied in 25% steps then the effective reduction of simultaneous study requires only 66 mixtures eliminating 54 duplicate experiments. If studied in 20% increments, 102 mixtures are required eliminating 66 redundant experiments.

A quaternary gradient representing a full range study of four factors (ABCD) forms a tetrahedron. Sixteen such tetrahedra can be combined into a four-dimensional figure that demonstrates all possible combinations of an ABCDA'B'C'D' system. Each tetrahedron will share all four of its faces and all six of its edges. The reduction in experimental space size as compared to individual experiments on each of the quaternary systems is substantial.

Many systems involve more than three or four factors and many systems have unequal numbers of factors. The reduction according to the invention is applicable to such systems. For example, a polymer resin study can have mono-functional (type "A"), di-functional (type "B") and tri-functional (type "C") monomers combined in mixtures. The system may include four examples of mono-functional (A^1, A^2, A^3, A^4), five examples of di-functional (B^1, B^2, B^3, B^4, B^5) and two examples of tri-functional (C^1 and C^2) monomers. The minimum number of runs needed for overlapping ternary systems $A^1B^1C^1A^2B^2C^2 \dots A^{(n_A)}B^{(n_B)}C^{(n_C)}$ or quaternary systems, $A^1B^1C^1D^1A^2B^2C^2D^2 \dots A^{(n_A)}B^{(n_B)}C^{(n_C)}D^{(n_D)}$, where n_A, n_B , etc. are equal to the number of monomers of types A, B, etc. can be studied simultaneously in a minimum number of experiments, which can be determined from TABLE 1 and the following algorithm.

TABLE 1

T	= total <u>number of types of factors</u> or reagents. T = 3 for a ternary system, T=4 for a quaternary system, etc.
n_T	= number of factors or reagents of type "T"
$Q_T = n_1 \times n_2 \times n_3 \times n_4 \times \dots \times n_T$	= number of separate T-dimensional gradients needed if overlapping not used
$V = n_1 + n_2 + n_3 + n_4 + \dots + n_T$	= number of vertices needed when overlapping used.
M	= the number of intervals from 0 to 100%, inclusive, for each factor (M = 6 for intervals = 20%)
$E_T = \frac{M \times (M+1) \times (M+2) \times \dots \times (M+T-2)}{1 \times 2 \times 3 \times \dots \times (T-1)}$	= total number of experiments needed for a single space with T types and M intervals
$I_T = \frac{(M-2) \times (M-3) \times \dots \times (M-T)}{1 \times 2 \times \dots \times (T-1)}$	= total number of experiments needed for the "T-way" combinations of factors of a single space with T types and M intervals

$Q_T \times E_T$ = number of experiments needed if all gradients are run without overlap

Ternary:

$$V + \prod_{i=1}^3 n_i \times I_3 + \left[\sum_{i=1}^3 \frac{1}{n_i} \prod_{i=1}^3 n_i \right] \times I_2$$

- 5 The total number of experiments (the experimental space) needed in a quaternary and pentanary systems with overlapping are as follows:

Quaternary:

$$V + \prod_{i=1}^4 n_i \times I_4 + \left[\sum_{i=1}^4 \frac{1}{n_i} \prod_{i=1}^4 n_i \right] \times I_3 + \left[\sum_{i=1}^4 \sum_{j=i+1}^4 \frac{1}{n_i n_j} \prod_{i=1}^4 n_i \right] \times I_2$$

10

Pentanary:

$$V + \prod_{i=1}^5 n_i \times I_5 + \left[\sum_{i=1}^5 \frac{1}{n_i} \prod_{i=1}^5 n_i \right] \times I_4 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \frac{1}{n_i n_j} \prod_{i=1}^5 n_i \right] \times I_3 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \sum_{k=j+1}^5 \frac{1}{n_i n_j n_k} \prod_{i=1}^5 n_i \right] \times I_2$$

- 15 The algorithm described in TABLE 2 represents a minimum experimental space for any mixture system of 2 or more types of factors.

TABLE 2

First Term	V
Second Term	$\prod_{i=1}^T n_i \times I_T$
The Third and subsequent terms consist of the product of three expressions (as shown in brackets here)	$\left(\sum_{i=1}^T \frac{1}{n_i} \right) \times \left(\prod_{i=1}^T n_i \right) \times [I_{(T-1)}]$

Each subsequent term is created from the previous term by:

1. Decrementing the subscript on I (e.g. $I_{(T-1)} \rightarrow I_{(T-2)}$) in the third expression
2. Not changing the second expression
3. In the first expression,
 - Adding an additional summation, incremented over another index (e.g. $i \rightarrow j$) from a starting point one unit higher than the first summation. e.g.

$$\sum_{i=1} \rightarrow \sum_{i=1} \sum_{j=i+1}$$

- Adding a value of n, indexed by the next index, to the inverse term. e.g.

$$\frac{1}{n_i} \rightarrow \frac{1}{n_i n_j}$$

While the invention advantageously defines a minimum experimental space for any mixture experiment, the invention is of particular advantage in defining experimental space for a high throughput screening (HTS) of mixtures. Particularly, the invention is directed to a method and system for defining an experimental space and conducting a combinatorial high throughput screening (CHTS) of the experimental space to determine a best case set of reaction factors.

In experimental reaction systems, each potential combination of reactant, catalyst and condition must be evaluated in a manner that provides correlation to performance in a production scale reactor. Combinatorial organic synthesis (COS) is a high throughput screening (HTS) methodology that was developed for pharmaceuticals. COS uses systematic and repetitive synthesis to produce diverse

5 molecular entities formed from sets of chemical "building blocks." As with traditional research, COS relies on experimental synthesis methodology. However, instead of synthesizing a single compound, COS exploits automation and miniaturization to produce large libraries of compounds through successive stages, each of which produces a chemical modification of an existing molecule of a preceding stage. A library is a physical, trackable collection of samples resulting from a definable set of processes or reaction steps. The libraries comprise compounds that can be screened for various activities.

10 Typically, a CHTS method is characterized by parallel reactions at a micro scale. In one aspect, CHTS can be described as a method comprising (A) an iteration of steps of (i) selecting a set of reactants; (ii) reacting the set and (iii) evaluating a set of products of the reacting step and (B) repeating the iteration of steps (i), (ii) and (iii) wherein a successive set of reactants selected for a step (i) is chosen as a result of an evaluating step (iii) of a preceding iteration.

15 In another typical CHTS method, a multiplicity of tagged reactants is subjected to an iteration of steps of (A) (i) simultaneously reacting the reactants, (ii) identifying a multiplicity of tagged products of the reaction and (B) evaluating the identified products after completion of a single or repeated iteration (A).

20 A typical CHTS can utilize advanced automated, robotic, computerized and controlled loading, reacting and evaluating procedures.

25 In one embodiment, the method of the invention can comprise (A) defining a first experimental space comprising factors of at least two mixtures with at least one common factor, (B) defining a second experimental space by deleting duplicate factor combinations from the first experimental space, (C) (a) reacting a reactant selected from the second experimental space under a set of catalysts or reaction conditions selected from the second experimental space and (b) evaluating a set of products of the reacting step and (D) reiterating step (C) wherein a next second experimental space selected for a step (a) is chosen as a result of an evaluating step (b) of a preceding iteration of step (C).

In this embodiment, the invention can be applied to study a process for preparing diaryl carbonates. Diaryl carbonates such as diphenyl carbonate can be prepared by reaction of hydroxyaromatic compounds such as phenol with oxygen and carbon monoxide in the presence of a catalyst composition comprising a Group VIII B metal such as palladium or a compound thereof, a bromide source such as a quaternary ammonium or hexaalkylguanidinium bromide and a polyaniline in partially oxidized and partially reduced form. The invention can be applied to screen for a catalyst to prepare a diaryl carbonate by carbonylation.

Various methods for the preparation of diaryl carbonates by a carbonylation reaction of hydroxyaromatic compounds with carbon monoxide and oxygen have been disclosed. The carbonylation reaction requires a rather complex catalyst. Reference is made, for example, to Chaudhari et al., U.S. Pat. 5,917,077. The catalyst compositions described therein comprise a Group VIII B metal (i.e., a metal selected from the group consisting of ruthenium, rhodium, palladium, osmium, iridium and platinum) or a complex thereof.

The catalyst material also includes a bromide source. This may be a quaternary ammonium or quaternary phosphonium bromide or a hexaalkylguanidinium bromide. The guanidinium salts are often preferred; they include the α , ω -bis(pentaalkylguanidinium)alkane salts. Salts in which the alkyl groups contain 2-6 carbon atoms and especially tetra-n-butylammonium bromide and hexaethylguanidinium bromide are particularly preferred.

Other catalytic constituents are necessary in accordance with Chaudhari et al. The constituents include inorganic cocatalysts, typically complexes of cobalt(II) salts with organic compounds capable of forming complexes, especially pentadentate complexes. Illustrative organic compounds of this type are nitrogen-heterocyclic compounds including pyridines, bipyridines, terpyridines, quinolines, isoquinolines and biquinolines; aliphatic polyamines such as ethylenediamine and tetraalkylethylenediamines; crown ethers; aromatic or aliphatic amine ethers such as cryptanes; and Schiff bases. The especially preferred inorganic cocatalyst in many instances is a cobalt(II) complex with bis-3-(salicylamino)propylmethylamine.

Organic cocatalysts may be present. These cocatalysts include various terpyridine, phenanthroline, quinoline and isoquinoline compounds including 2,2':6',2''-terpyridine, 4-methylthio-2,2':6',2''-terpyridine and 2,2':6',2''-terpyridine N-oxide, 1,10-phenanthroline, 2,4,7,8-tetramethyl-1,10-phenanthroline, 4,7-diphenyl-1,10-phenanthroline and 3,4,7,8-tetramethyl-1,10-phenanthroline. The terpyridines and especially 2,2':6',2''-terpyridine are preferred.

Another catalyst constituent is a polyaniline in partially oxidized and partially reduced form.

Any hydroxyaromatic compound may be employed. Monohydroxyaromatic compounds, such as phenol, the cresols, the xylenols and p-cumylphenol are preferred with phenol being most preferred. The method may be employed with dihydroxyaromatic compounds such as resorcinol, hydroquinone and 2,2-bis(4-hydroxyphenyl)propane or "bisphenol A," whereupon the products are polycarbonates.

Other reagents in the carbonylation process are oxygen and carbon monoxide, which react with the phenol to form the desired diaryl carbonate.

These and other features will become apparent from the drawings and following detailed discussion, which by way of example without limitation describe preferred embodiments of the present invention.

Example

This example illustrates an identification of an active and selective catalyst for the production of aromatic carbonates. The method identifies a best cocatalyst from a complex chemical space, where the chemical space is defined as an assemblage of all possible ratios of combinations of certain Group IVb, Group VIb, and Lanthanide Group metal complexes. The chemical space consists of the following chemical factors of TABLE 3:

TABLE 3

Group IVb complex	Group VIb complex	Lanthanide complex
Ti(acac) ₂	Cr(acac) ₃	Ce(acac) ₃
Zr(acac) ₂	Mo(acac) ₃	Eu(acac) ₃

The combinations that are sampled are shown in TABLE 4.

TABLE 4

ABC	ABC'	AB'C	A'BC	AB'C'	A'BC'	A'B'C	A'B'C'
Ti(acac) ₂ C	Ti(acac) ₂ C	Ti(acac) ₂ M	Zr(acac) ₂ C	Ti(acac) ₂ M	Zr(acac) ₂ C	Zr(acac) ₂ M	Zr(acac) ₂ M
r(acac) ₃ Ce(acac) ₃	r(acac) ₃ Eu(acac) ₃	o(acac) ₃ Ce(acac) ₃	r(acac) ₃ Ce(acac) ₃	o(acac) ₃ Eu(acac) ₃	r(acac) ₃ Eu(acac) ₃	o(acac) ₃ Ce(acac) ₃	o(acac) ₃ Eu(acac) ₃

To sample the possible ratios of the factors as finely as possible, they are arranged in a well-known ternary gradient with 20% steps of each factor as shown in FIG. 6. FIG. 6 shows an ABC system. Each intersection of the lines in the gradient represents one mixture to be tested. There are thus 21 mixtures to be tested in the ABC system, and 8 x 21 = 168 mixtures in the entire system before application of the procedures described in the invention. By application of the invention, only the 102 unique mixtures of the 168 mixtures are required to be tested. This represents a 39.3% reduction in experimental space. The 102 runs are given in TABLE 5, where values are in ppm.

TABLE 5

Mixture	Ti(acac) ₂	Cr(acac) ₃	Ce(acac) ₃	Zr(acac) ₂	Mo(acac) ₃	Eu(acac) ₃	TON
1	0	0	0	100	0	0	1149
2	0	0	20	80	0	0	954
3	0	0	40	60	0	0	467
4	0	0	60	40	0	0	779
5	0	0	80	20	0	0	635
6	0	0	100	0	0	0	824
7	0	20	0	80	0	0	445
8	0	20	20	60	0	0	386
9	0	20	40	40	0	0	1091
10	0	20	60	20	0	0	727
11	0	20	80	0	0	0	515
12	0	40	0	60	0	0	850
13	0	40	20	40	0	0	323
14	0	40	40	20	0	0	393
15	0	40	60	0	0	0	903
16	0	60	0	40	0	0	1018
17	0	60	20	20	0	0	983
18	0	60	40	0	0	0	1053
19	0	80	0	20	0	0	505
20	0	80	20	0	0	0	463
21	0	100	0	0	0	0	708
22	0	0	0	80	0	20	501
23	0	20	0	60	0	20	1113
24	0	40	0	40	0	20	959
25	0	60	0	20	0	20	481
26	0	80	0	0	0	20	953
27	0	0	0	60	0	40	744
28	0	20	0	40	0	40	723
29	0	40	0	20	0	40	1106
30	0	60	0	0	0	40	360
31	0	0	0	40	0	60	490
32	0	20	0	20	0	60	751
33	0	40	0	0	0	60	718
34	0	0	0	20	0	80	472
35	0	20	0	0	0	80	760
36	0	0	0	0	0	100	1300
37	0	0	0	80	20	0	893
38	0	0	20	60	20	0	480
39	0	0	40	40	20	0	350
40	0	0	60	20	20	0	330
41	0	0	80	0	20	0	1202
42	0	0	0	60	20	20	615
43	0	0	0	40	20	40	1056
44	0	0	0	20	20	60	1060
45	0	0	0	0	20	80	1149

46	0	0	0	60	40	0	452
47	0	0	20	40	40	0	536
48	0	0	40	20	40	0	640
49	0	0	60	0	40	0	852
50	0	0	0	40	40	20	713
51	0	0	0	20	40	40	1186
52	0	0	0	0	40	60	913
53	0	0	0	40	60	0	816
54	0	0	20	20	60	0	508
55	0	0	40	0	60	0	760
56	0	0	0	20	60	20	658
57	0	0	0	0	60	40	1341
58	0	0	0	20	80	0	882
59	0	0	20	0	80	0	381
60	0	0	0	0	80	20	728
61	0	0	0	0	100	0	412
62	20	0	80	0	0	0	393
63	20	20	60	0	0	0	909
64	20	40	40	0	0	0	1092
65	20	60	20	0	0	0	516
66	20	80	0	0	0	0	777
67	20	60	0	0	0	20	548
68	20	40	0	0	0	40	465
69	20	20	0	0	0	60	1212
70	20	0	0	0	0	80	907
71	20	0	60	0	20	0	580
72	20	0	0	0	20	60	3557
73	20	0	40	0	40	0	1003
74	20	0	0	0	40	40	4238
75	20	0	20	0	60	0	858
76	20	0	0	0	60	20	3337
77	20	0	0	0	80	0	1426
78	40	0	60	0	0	0	520
79	40	20	40	0	0	0	623
80	40	40	20	0	0	0	414
81	40	60	0	0	0	0	477
82	40	40	0	0	0	20	622
83	40	20	0	0	0	40	1130
84	40	0	0	0	0	60	1405
85	40	0	40	0	20	0	1327
86	40	0	0	0	20	40	4605
87	40	0	20	0	40	0	886
88	40	0	0	0	40	20	4531
89	40	0	0	0	60	0	1308
90	60	0	40	0	0	0	1159
91	60	20	20	0	0	0	750
92	60	40	0	0	0	0	711
93	60	20	0	0	0	20	1052

94	60	0	0	0	0	40	1133
95	60	0	20	0	20	0	1202
96	60	0	0	0	20	20	3908
97	60	0	0	0	40	0	1238
98	80	0	20	0	0	0	750
99	80	20	0	0	0	0	675
100	80	0	0	0	0	20	848
101	80	0	0	0	20	0	1439
102	100	0	0	0	0	0	432

Catalyst mixtures are made up in phenol solvent containing the following factors of TABLE 6 and the cocatalyst mixture using the concentrations of each factor as given in the rows of TABLE 6. The total volume of each catalyst mixture is 1.0 ml. From each mixture, a 25 microliter aliquot is dispensed into a 2 ml reaction vial, forming a film on the bottom. The vials are subjected to 1000 psi pressure at 100° C for 120 min. At the end of the reaction time, the system is cooled and depressurized and the contents of each vial are analyzed for diphenyl carbonate product using conventional gas chromatographic methods. The turnover number (TON) for each reaction is calculated as (mols of diphenylcarbonate/mols of primary catalyst). The results are given in the column TON of TABLE 5.

TABLE 6

Primary Catalyst:	Pd(acac)₂	25 ppm
Anion Cocatalyst	(Et₃N)Br	800 ppm

A histogram, FIG. 7, depicting the number of the 102 experiments which fall into certain ranges of Turnover Number (TON), shows that there are five unusually high values (>1500 TON), which are associated with runs 72, 74, 76, 86, 88, and 96. Examination of these runs shows that they all contain the ternary combination:

5 Ti(acac)₂, Mo(acac)₃, and Eu(acac)₃. The effect of the three way combination of Ti(acac)₂, Mo(acac)₃, and Eu(acac)₃ is further demonstrated in Figures 8-10. Each of these 3-D bar charts corresponds to one of the 8 ternaries listed in TABLE 4. The vertical (Z) axis depicts the TON response and the X and Y axes the relative amounts of two of the three reactant mixtures in the ternary. Since the total amount of all three reactants equals a constant value (100 ppm in this case), the third reactant proportion for a given TON is equal to 100 minus the sum of the values of the other two reactants for that TON. These charts show that the full complement of ternaries can be constructed using the reduced space of the invention and that areas of high activity can be delineated using the technique.

10 While preferred embodiments of the invention have been described, the present invention is capable of variation and modification and therefore should not be limited to the precise details of the Examples. For example, the invention is applicable to a wide variety of experimental systems where multiple mixtures of components with common elements must be studied in gradients. Examples of such systems include organic systems such as polymers, coatings and adhesives and inorganic systems such as phosphors and scintillators and even metal systems such as alloys.

15 The invention includes changes and alterations that fall within the purview of the following claims.

20

CLAIMS:

What is claimed is:

1. A method, comprising:

(A) defining a first experimental space comprising factors of at least two mixtures with at least one common factor;

5 (B) defining a second experimental space by deleting duplicate factor combinations from said first experimental space; and

(C) conducting an experiment on said second experimental space.

2. The method of claim 1, wherein (C) comprises effecting a combinatorial high throughput screening (CHTS) to select a best case set of factors
10 from said second experimental space.

3. The method of claim 2, wherein said CHTS comprises effecting parallel chemical reactions of an array of reactants defined by said second experimental space.

4. The method of claim 2, wherein said CHTS comprises effecting
15 parallel chemical reactions on a micro scale on reactants defined as said second experimental space.

5. The method of claim 2, wherein (C) comprises an iteration of steps of simultaneously reacting a multiplicity of tagged reactants and identifying a multiplicity of tagged products of the reaction and evaluating said identified products
20 after completion of a single or repeated iteration.

6. The method of claim 1, wherein said second experimental space is defined by two or more factors, each having a plurality of possible identities.

7. The method of claim 1, wherein said second experimental space factors comprise reactants, catalysts and conditions and said (C) comprises (a) reacting a reactant selected from the second experimental space under a set of catalysts or
25

reaction conditions selected from the second experimental space and (b) evaluating a set of products of the reacting step and further comprising (D) reiterating step (C) wherein a next second experimental space selected for a step (a) is chosen as a result of an evaluating step (b) of a preceding iteration of step (C).

8. The method of claim 7, comprising reiterating (C) until a best set of factors of said second experimental space is selected.

9. The method of claim 1, wherein said first experimental space includes a catalyst system comprising combinations of Group IVB, Group VIB and Lanthanide Group metal complexes.

10. The method of claim 1, wherein said second experimental space includes a catalyst system comprising a Group VIII B metal.

11. The method of claim 1, wherein said second experimental space includes a catalyst system comprising palladium.

12. The method of claim 1, wherein said second experimental space includes a catalyst system comprising a halide composition.

13. The method of claim 1, wherein said second experimental space includes an inorganic co-catalyst.

14. The method of claim 1, wherein said second experimental space includes a catalyst system that includes a combination of inorganic co-catalysts.

15. The method of claim 1, wherein said second experimental space is a ternary space comprising a number of experiments defined by

$$V + \prod_{i=1}^3 n_i \times I_3 + \left[\sum_{i=1}^3 \frac{1}{n_i} \prod_{i=1}^3 n_i \right] \times I_2$$

16. The method of claim 1, wherein said second experimental space is a quaternary space comprising a number of experiments defined by

$$V + \prod_{i=1}^4 n_i \times I_4 + \left[\sum_{i=1}^4 \frac{1}{n_i} \prod_{i=1}^4 n_i \right] \times I_3 + \left[\sum_{i=1}^4 \sum_{j=i+1}^4 \frac{1}{n_i n_j} \prod_{i=1}^4 n_i \right] \times I_2$$

17. The method of claim 1, wherein said second experimental space is a pentanary space comprising a number of experiments defined by

$$V + \prod_{i=1}^5 n_i \times I_5 + \left[\sum_{i=1}^5 \frac{1}{n_i} \prod_{i=1}^5 n_i \right] \times I_4 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \frac{1}{n_i n_j} \prod_{i=1}^5 n_i \right] \times I_3 +$$

$$\left[\sum_{i=1}^5 \sum_{j=i+1}^5 \sum_{k=j+1}^5 \frac{1}{n_i n_j n_k} \prod_{i=1}^5 n_i \right] \times I_2$$

18. A system for selecting a best case set of experiments of a experimental reaction, comprising;

a processor that (A) defines a first experimental space comprising factors of at least two mixtures with at least one common factor and (B) defines a second experimental space by deleting duplicate factor combinations from said first experimental space; and

a reactor and evaluator to select a best case set of factors from said experimental space by a combinatorial high throughput screening (CHTS) method to select a best case set of factors from said experimental space.

19. The system of claim 18, wherein said processor comprises

a display terminal having screen displays whereby a researcher can input values for factors on said screen;

a database for storing said factors;

a computer for generating a set of test cases for a set of said factors based on a researcher specified value for identifying a number of interacting relationships within said factors;

a computer combining said test cases for set of factors with said relationships and providing a merged table of test cases; and

an output for writing to a database said merged table of test cases.

20. The system of claim 18, wherein said second experimental space is a ternary space comprising a number of experiments defined by

$$V + \prod_{i=1}^3 n_i \times I_3 + \left[\sum_{i=1}^3 \frac{1}{n_i} \prod_{i=1}^3 n_i \right] \times I_2$$

21. The system of claim 18, wherein said second experimental space is a quaternary space comprising a number of experiments defined by

$$V + \prod_{i=1}^4 n_i \times I_4 + \left[\sum_{i=1}^4 \frac{1}{n_i} \prod_{i=1}^4 n_i \right] \times I_3 + \left[\sum_{i=1}^4 \sum_{j=i+1}^4 \frac{1}{n_i n_j} \prod_{i=1}^4 n_i \right] \times I_2$$

22. The system of claim 18, wherein said second experimental space is a pentenary space comprising a number of experiments defined by

$$V + \prod_{i=1}^5 n_i \times I_5 + \left[\sum_{i=1}^5 \frac{1}{n_i} \prod_{i=1}^5 n_i \right] \times I_4 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \frac{1}{n_i n_j} \prod_{i=1}^5 n_i \right] \times I_3 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \sum_{k=j+1}^5 \frac{1}{n_i n_j n_k} \prod_{i=1}^5 n_i \right] \times I_2$$

23. An experimental space, comprising a number of mixture combinations defined by an algorithm, which expresses the sum of terms:

$$V + \prod_{i=1}^T n_i \times I_T + \left(\sum_{i=1}^T \frac{1}{n_i} \right) \times \left(\prod_{i=1}^T n_i \right) \times [I_{(T-1)}]$$

for a ternary system ($T = 3$) or an algorithm for a succeeding T -nary system, determined from a previous term by: (a) adding an additional term which contains an additional summation, incremented over a next index from a starting point one unit

higher than the first summation ; (b) decrementing the subscript on I ; and (c) adding a value of n , indexed by the next index, to the inverse term.

24. The experimental space of claim 23, comprising a number of mixture combinations defined by an algorithm, which expresses the sum of terms:

$$5 \quad V + \prod_{i=1}^4 n_i \times I_4 + \left[\sum_{i=1}^4 \frac{1}{n_i} \prod_{i=1}^4 n_i \right] \times I_3 + \left[\sum_{i=1}^4 \sum_{j=i+1}^4 \frac{1}{n_i n_j} \prod_{i=1}^4 n_i \right] \times I_2$$

for a quaternary system.

25. The experimental space of claim 23, comprising a number of mixture combinations defined by an algorithm, which expresses the sum of terms:

$$10 \quad V + \prod_{i=1}^5 n_i \times I_5 + \left[\sum_{i=1}^5 \frac{1}{n_i} \prod_{i=1}^5 n_i \right] \times I_4 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \frac{1}{n_i n_j} \prod_{i=1}^5 n_i \right] \times I_3 + \left[\sum_{i=1}^5 \sum_{j=i+1}^5 \sum_{k=j+1}^5 \frac{1}{n_i n_j n_k} \prod_{i=1}^5 n_i \right] \times I_2$$

for a pentanary system.

METHOD FOR DEFINING AN EXPERIMENTAL SPACE AND METHOD
AND SYSTEM FOR CONDUCTING COMBINATORIAL HIGH THROUGHPUT
SCREENING OF MIXTURES

ABSTRACT OF THE DISCLOSURE

5 A method comprises (A) defining a first experimental space comprising
factors of at least two mixtures with at least one common factor, (B) defining a second
experimental space by deleting duplicate factor combinations from the first
experimental space and (C) conducting an experiment on the second experimental
space. A system comprises a processor that (A) defines a first experimental space
comprising factors of at least two mixtures with at least one common factor and (B)
defines a second experimental space by deleting duplicate factor combinations from
the first experimental space. The system also comprises a reactor and evaluator to
select a best case set of factors from the second experimental space by a combinatorial
10 high throughput screening (CHTS) method to select a best case set of factors from the
second experimental space.

003207-12036960




FIG. 1

FIG. 2





FIG. 3






FIG. 4




FIG. 5

FIG. 6




FIG. 7





FIG. 8




FIG. 9




FIG. 10

DECLARATION FOR PATENT APPLICATION

Docket Number

RD-28,030

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**METHOD FOR DEFINING AN EXPERIMENTAL SPACE AND METHOD AND SYSTEM FOR CONDUCTING
COMBINATORIAL HIGH THROUGHPUT SCREENING OF MIXTURES**

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International Application Number _____
and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56. I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application

Priority Claimed

☐ Yes ☐ No☐ Yes ☐ No

(Number)

(Country)

(Day/Month/Year Filed)

(Number)

(Country)

(Day/Month/Year Filed)

I hereby claim the benefit under Title 35, United States Code, §119(e) of any **United States provisional application(s)** listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

I hereby claim the benefit under Title 35, United States Code §120 of any **United States Application(s)** listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Number)

(Filing Date)

(Status - patented, pending, abandoned)

(Application Number)

(Filing Date)

(Status - patented, pending, abandoned)

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, **CUSTOMER NO. 006147.**

Douglas E. Stoner, Reg. No. 26,509, Marvin Snyder, Reg. No. 20,126, Donald S. Ingraham, Reg. No. 33,714, Jill M. Breedlove, Reg. No. 32,684, Noreen C. Johnson, Reg. No. 38,929, Ronald E. Myrick, Reg. No. 26,315, Henry J. Policinski, Reg. No. 26,621, Jay L. Chaskin, Reg. No. 24,030, James W. Mitchell, Reg. No. 25,602, Bernard Snyder, Reg. No. 24,843 and Catherine J. Winter, Reg. No. 38,364.

Address all telephone calls to: Noreen C. Johnson at telephone number (518) 387-7863

Address all correspondence to: **General Electric Company
CRD Patent Docket Rm 4A59
P.O. Box 8, Bldg. K-1 - Salamone
Schenectady, New York 12301**

**006147**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SOLE OR FIRST INVENTOR:

Full name: James Norman Cawse

First Name

Middle Name

Last Name

Signature: *James Norman Cawse*

Date

10/16/2000Residence: Pittsfield, MA

City and State

Citizenship: USAPost Office Address: 132 Kittredge Road, Pittsfield, MA 01201

SECOND JOINT INVENTOR:

Full name: Ronald James Wroczynski

First Name

Middle Name

Last Name

Signature: *Ronald James Wroczynski*

Date

10-16-2000Residence: Schenectady, NY

City and State

Citizenship: USAPost Office Address: 209 Vincenza Lane, Schenectady, NY 12303

THIRD JOINT INVENTOR:

Full name: Darchun Billy Yang

First Name

Middle Name

Last Name

Signature: *Darchun Billy Yang*

Date

October 20, 2000
October 20, 2000Residence: San Dimas, CA

City and State

Citizenship: USAPost Office Address: 2226 Calle Escarlata, San Dimas, CA 91773

FOURTH JOINT INVENTOR:

Full name: _____

First Name

Middle Name

Last Name

Signature: _____

Date

Residence: _____

City and State

Citizenship: _____

Post Office Address: _____